

System Requirements Commercial & Digital Printing

OneVision Software AG

Content

Speedflow Check 10.0, Speedflow Check Plus 10.0, Speedflow Edit 10.0 (Windows),	2
Speedflow Recompose 10.0.....	2
Speedflow Edit 10.0 (Macintosh OSX).....	2
Speedflow Impose 4.0.....	2
Speedflow Cockpit 3.2.....	3
Sicuriq 1.5, Sicuriq Pro 1.5.....	4

Speedflow Check 10.0, Speedflow Check Plus 10.0, Speedflow Edit 10.0 (Windows), Speedflow Recompose 10.0

Operating system	Windows XP Professional®, Service Pack 2, 32 Bit Windows Server 2003® Standard Edition Service Pack 2, 32 Bit Windows Server 2003 R2® Standard Edition Service Pack 2, 32 Bit Windows Server 2003 R2® Standard Edition Service Pack 2, 64 Bit Windows Server 2008® Standard Edition Service Pack 2, 32 Bit Windows Server 2008® Standard Edition Service Pack 2, 64 Bit (HASP dongle only)
Processor	Intel Core 2 Duo 2,4 GHz (or faster), 1066 MHz FSB (or faster), AMD Athlon 64 x2 5200+ (or compatible/or faster),
Main memory	4 GB RAM or more recommended on 64 Bit OS 8 GB RAM or more recommended
Hard disk	Fast hard disk, 50 GB available to accommodate installation and virtual memory, RAID 5 or other redundancy recommended, 50 GB free disk space for temporary data (normally on C:)
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle
Networking	TCP/IP services and active network connection required

Speedflow Edit 10.0 (Macintosh OSX)

Operating system	Mac OS X 10.4.11 with Java for Mac OS X 10.4 Release 9 Mac OS X 10.5.8 with Java for Mac OS X 10.5 Update 5
Processor	Apple Macintosh with PowerPC G5 1,4 GHz or faster or Intel CPU
Main memory	4 GB RAM or more recommended
Hard disk	Fast hard disk, 30 GB available to accommodate installation and virtual memory
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle
Networking	TCP/IP services and active network connection required

Speedflow Impose 4.0

Operating system	Windows XP Professional®, Service Pack 2, 32 Bit Windows Server 2003® Standard Edition, Service Pack 2, 32 Bit Windows Vista Business®, Service Pack 1, 32 Bit
Processor	Intel Pentium 2 GHz (or faster)
Main memory	1024 MB RAM or more recommended
Hard disk	Fast hard disk, 30 GB available to accommodate installation and virtual memory
Resolution	Support for 24-bit color at 1024 x 768 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle

Speedflow Cockpit 3.2

Operating system	Windows 2000 Professional® or Server®, Service Pack 4, Windows XP Professional®, Service Pack 2, 32 Bit Windows Server 2003® Standard Edition Service Pack 1, 32 Bit
Processor	Intel Pentium IV 2,8 GHz DualCore (or faster), 533 MHz FSB (or faster) recommended AMD Athlon 64 X2 3800+ (or compatible/or faster), recommended
Main memory	2048 MB RAM or more recommended
Hard disk	Fast hard disk, 100 GB available to accommodate installation, virtual memory and file storage
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle
Networking	TCP/IP services and active network connection required

License dongles for Speedflow Cockpit and JDFnet require separate USB ports (two dongles are included).

Speedflow Control, Speedflow Interact, and Speedflow AutoImpose – all modules of Speedflow Cockpit – do not require separate license dongles/USB ports.

Speedflow Control 3.2 (Windows), Speedflow Interact 3.2 (Windows)

Operating system	Windows 2000 Professional® or Server®, Service Pack 4, Windows XP Professional®, Service Pack 2, 32 Bit Windows Server 2003® Standard Edition Service Pack 1, 32 Bit
Processor	Intel Pentium IV 2.8 GHz or faster, 533 MHz FSB recommended (Hyperthreading currently not supported) AMD Athlon 64 3000+ or compatible/or faster,
Main memory	2048 MB RAM or more recommended
Hard disk	Fast hard disk, 30 GB available to accommodate installation, virtual memory and file storage
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
Networking	TCP/IP services and active network connection required

Speedflow Control 3.2 (Macintosh OSX), Speedflow Interact 3.2 (Macintosh OSX)

Operating system	Mac OS X 10.4.11 with Java for Mac OS X 10.4 Release 5 Mac OS X 10.5 currently not supported
Processor	Apple Macintosh with PowerPC G5 1 GHz or faster Intel based Macintosh systems
Main memory	2048 MB RAM or more recommended
Hard disk	Fast hard disk, 30 GB available to accommodate installation and virtual memory
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
Networking	TCP/IP services and active network connection required

Sicuriq 1.5, Sicuriq Pro 1.5

Operating system	Windows 2000 Professional® or Server®, Service Pack 4, Windows XP Professional®, Service Pack 2, 32 Bit, Windows Server 2003® Standard Edition Service Pack 1, 32 Bit
Processor	Intel Core 2 Duo (or compatible) 2 GHz or faster
Main memory	2048 MB RAM or more recommended
Hard disk	Fast hard disk, 10 GB available to accommodate installation and virtual memory
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle
Networking	TCP/IP services and active network connection required

